

PUBLIC TECHNICAL DATASHEET 03 | EDITION 1.2 | SEPTEMBER 2026

LifeBot Command

Remote clinical workstation family | DREAMS 12.07.15



LifeBot Command laptop illustration. Rugged, desktop and medical-cart arrangements are available.

Command gives authorized physicians and specialists a clinical workspace for consultation with selected Link or Core encounters. It combines shared patient context, monitoring information, medical media and communication with the local team.

Arrangement	Reference platform	Workspace selections
Portable workstation	Dell Pro Rugged 13 RA13250	Integrated display; selected radios, camera/audio, batteries and dock
Desktop workstation	Dell Pro Micro Plus	Customer-selected touchscreen(s), camera/audio and desk mount
Medical-cart workstation	Dell Pro Micro Plus	Customer-selected touchscreen(s), cart, mounts, power and peripherals

Application and clinical role

DREAMS version 12.07.15, build 3. Command is a Windows application, used locally or in a hosted virtual-machine arrangement. It supports selected encounter review, consultation audio/video, shared vitals/ECG and medical media, available camera control and consultation documentation.

All monitors supplied with desktop and medical-cart Command arrangements are touchscreens. Their sizes, the equipment included and the power arrangement are specified separately for each customer.

Each workstation configuration is defined by its selected host, displays, peripherals and power package.

PUBLIC TECHNICAL DATASHEET 03 | EDITION 1.2 | SEPTEMBER 2026

Command rugged reference

Dell Pro Rugged 13 RA13250 host family

Host characteristic	OEM reference specification
Processor options	Intel Core Ultra 5 135U, Ultra 7 165U or Ultra 7 165H
Memory	16 GB, 32 GB or 64 GB LPDDR5x, 6400 MT/s; processor-dependent options
Storage	Selected PCIe NVMe SSD; OEM configurations up to 2 TB
Display	13.3-inch FHD touch; 1920 × 1080; 60 Hz; 1400 nits; anti-glare
Host dimensions	324 × 220 × 36.5 mm (W × D × H)
Host starting weight	2.4 kg; selected options and accessories add mass
Battery options	53.5 Wh battery modules; supports up to two hot-swappable batteries
Adapter options	65 W or 100 W USB-C, selected for the processor/configuration
Network / radios	RJ45 Ethernet; selected Wi-Fi 6E/7; optional LTE/5G and GPS
I/O family	USB-A, Thunderbolt 4 / USB-C, HDMI, RS-232 and optional I/O bay
Camera / audio	Selected FHD RGB/IR camera, microphones, speakers and headset arrangement
Host ingress rating	IP65 for the OEM host under its specified use conditions

Select the processor, memory, storage, camera, radios, batteries, adapter and I/O options for the workstation. Define complete workstation runtime and operating limits for the assembled equipment package.

Component source: Dell Pro Rugged 13 RA13250 technical specifications, page 9. Exact connector versions follow the ordered host.

[Dell Pro Rugged 13 RA13250 specifications](#)

PUBLIC TECHNICAL DATASHEET 03 | EDITION 1.2 | SEPTEMBER 2026

Command desktop and cart

Dell Pro Micro Plus reference and deployment selections

Computer-only characteristic	Reference family
Reference model	Dell Pro Micro Plus QBM1250
Compute / memory	Intel Core Ultra options; up to 64 GB DDR5
Storage / network	Two M.2 SSD slots; 1 GbE RJ45; selected wireless card
Display / USB	Three DisplayPort outputs; six USB-A and two USB-C ports
Chassis only	182 × 36 × 178 mm (H × W × D); 1.22–1.43 kg
Host adapter options	130 W or 180 W; select for the ordered host

Local and hosted operation

Deployment area	Configuration detail
Application execution	Local Windows application or hosted Windows virtual machine
User workspace	Touchscreen sizes and quantity, input devices, camera/audio and viewing position
Remote access	Approved access method, identity, device/media redirection and network service
Clinical service	Consultation coverage, authorized roles, connected Link/Core locations and case workflow
Energy / support	Host adapter plus display/cart supply; UPS/runtime and service terms specified for the customer

The VM operating system, virtual CPU, RAM, storage and access solution are selected for the deployed service. They are distinct from the physical workstation specification. Screen size, included equipment and power remain customer-specific.

[Dell Pro Micro Plus QBM1250 specifications](#)

Specify network protocols, service ports and the remote device/media access method for the selected local or hosted arrangement.